

(19)



JAPANESE PATENT OFFICE

*Applicant's
exact claim
1 neg. electrode*

A1-5

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **11003707 A**

(43) Date of publication of application: **06 . 01 . 99**

(51) Int. Cl
H01M 4/58
H01M 4/02
H01M 4/04
H01M 10/40

(21) Application number: **09153981**

(22) Date of filing: **11 . 06 . 97**

(71) Applicant: **MATSUSHITA DENCHI KOGYO KK**
NIPPON TELEGR & TELEPH
CORP <NTT>

(72) Inventor: **HASEGAWA MASAKI**
YAMAURA JUNICHI
TSUTSUMI SHUJI
KONDO SHIGEO
YAMAKI JUNICHI
SAKURAI YOJI
MASASHIRO TAKAHISA
SAITO KEIICHI

(54) **LITHIUM SECONDARY BATTERY**

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a secondary battery with little deterioration in characteristics, even at high temperature storage by using a mono layer lithium - containing composite nitride having hexagonal system crystal structure as the negative active material.

SOLUTION: A lithium - containing composite nitride represented by formula, Li_3XMXN is used as a negative active material. In the formula, M represents and least one transition element selected from among the group

comprising Ti, V, Cr, Mn, Fe, Co, Ni, and Cu, and X represents a real number indicated by $0.1 \leq X \leq 0.8$. A nitride containing no lithium oxide and lithium hydroxide, which are impurities, is preferred. The nitride synthesized by having at least one kind of an alloy of lithium and the transition element M and an intermetallic compound of lithium and the transition element M react with nitrogen is referred. By raising the purity of the composite nitride, deterioration of battery characteristics at high temperature storage times can be retarded.

COPYRIGHT: (C)1999,JPO

BEST AVAILABLE COPY